



Hợp tác để thành công

**CÔNG TY CỔ PHẦN THƯƠNG MẠI VÀ SẢN XUẤT TOÀN AN KHÁNH**  
 Số 4, ngách 2, ngõ 199 Hồ Tùng Mậu, Cầu Diễn, Nam Từ Liêm, Hà Nội  
 Tel: 024 3227 2296  
 Email: contact@toanankhanh.com.vn, Web: www.toanankhanh.com.vn

### Technical Specification

Model	TAK - XY-FK32A	
Product function	<b>Main function</b>	Product picture
	32-inch touch screen, support 10 points capacitive touch function	
	7*24 hours ultra-stable industrial control host	
	Automatically read the second-generation ID card and extract the ID card document information (optional)	
	80mm thermal adhesive note printing	
Product performance		
Display screen	screen size	32inch
	LCD color	16. 7M
	W:H	16:09
	resolution ratio	1920(H)*1080(V)
Hardware configuration	CPU	I5
	hard disk	128GB
	internal storage	8G DDR3
	operating system	Windows10(test version)
External interface	LAN port	RJ45
	USB port	2
	AC supply hub	220V AC
communication	WIFI/BT	double frequency WIFI/BT4.1
	4G/3G	4G full Netcom
	RJ45	100M
QR code scanner(optional)	imaging sensor	640×480 CMOS : 120FPS
	illumination	White light LED (6500K)
	Symbologies	2D/1D
	Precision	≥5mil
	Bar code sensitivity**	Tilt ±55°, Spin±55°, rotate 360°
	communication interface	USB
	Operating voltage/current	5V DC±10% (typical) Less than 190mA (5V input) Less than 100mA (10V input)

<b>Built-in camera(optional)</b>	photosensitive element	CMOS
	articulation	200W pixel 1920*1080fhd
	Prime lens	
	articulation	
	Prime lens	7cm
	In vivo detection	PDF417, Data Matrix, QR Code
	bioassay	Interleaved 2 of 5, ISBN, Code 93, Code 11,UCC/EAN-128
		GS1 Databar, Matrix 2 of 5, Industrial 2 of 5,Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar,Standard 2 of 5, MSI-Plessey,GS1 composite code, so on.
<b>Operating environment</b>	output format	YUV/MJPEG.H.264
	white balance	automatic
	illuminance	Min 0.1LUX
<b>Storage environment</b>	temperature	5°C—40°C
	relative humidity	<80% (no condensation on the surface)
	temperature	-10°C—55°C
	relative humidity	<70% (no condensation on the surface)