


Technical Specification		
Model	TAK-XY-FKL238B	
Product function	Main function	
	23,8-inch touch screen, support 10 points capacitive touch function	
	7*24 hours ultra-stable industrial control host	
	IC/ID card reader (optional)	
	80mm thermal adhesive note printing	
	Highly sensitive QR code scanner	
Product performance		
Display screen	screen size	23,8inch
	LCD color	16 . 7M
	W:H	16:9
	resolution ratio	1920(H)*1080(V)
Hardware configuration	CPU	I5
	hard disk	128GB
	internal storage	8G DDR3
	operating system	Windows 10
External interface	LAN port	1
	USB port	2
	AC supply hub	220V AC
communication	WIFI/BT	double frequency WIFI/BT4.1
	4G/3G	4G full Netcom
	RJ45	100M
QR code scanner	imaging sensor	640×480 CMOS : 120FPS
	illumination	White light LED (6500K)
	Symbologies	2D/1D
	Precision	≥5mil
	Bar code sensitivity**	Tilt ±55° , Spin±55° , rotate 360°
	communication interface	USB
	Operating voltage/current	5V DC±10% (typical) Less than 190mA (5V input) Less than 100mA (10V input)
printer	80mm printer	support



Hợp tác để thành công

CÔNG TY CỔ PHẦN THƯƠNG MẠI VÀ SẢN XUẤT TOÀN AN KHÁNH

Số 4, ngách 2, ngõ 199 Hồ Tùng Mậu, Cầu Diễn, Nam Từ Liêm, Hà Nội

Hotline: 0986000358

Email: contact@toanankhanh.com.vn, Web: www.toanankhanh.com.vn

swiping card	ID card reader	Support	
Built-in camera	photosensitive element	CMOS	
	articulation Prime lens	200W pixel 1920*1080fhd	
	articulation Prime lens In vivo detection	7cm	PDF417, Data Matrix, QR Code
		bioassay	Interleaved 2 of 5, ISBN, Code 93, Code 11,UCC/EAN-128 GS1 Databar, Matrix 2 of 5, Industrial 2 of 5,Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar,Standard 2 of 5, MSI-Plessey,GS1 composite code, so on.
	output format	YUV/MJPEG.H.264	
	white balance	automatic	
	illuminance	Min 0.1LUX	
Operating environment	temperature	5°C—40°C	
	relative humidity	<80% (no condensation on the surface)	
Storage environment	temperature	-10°C—55°C	
	relative humidity	<70% (no condensation on the surface)	

