


| Technical Specification | | |
|-------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------|
| Model | TAK-XY-KB21 | |
| Product function | Main function |  |
| | 21.5inch touch screen | |
| | 7*24 hours ultra-stable industrial control host | |
| | IC card reader | |
| | 58mm thermal adhesive note printing | |
| | Highly sensitive QR code scanner | |
| Product performance | | |
| Display screen | screen size | 21.5inch |
| | resolution ratio | 1920*1080 IPS |
| Hardware configuration | CPU | I5- 4 |
| | hard disk | 512GB |
| | internal storage | 16G DDR3 |
| | operating system | Windows10(NON-GENUINE) |
| External interface | LAN port | 1 |
| | USB port | 2 |
| | AC supply hub | 220V AC |
| communication | WIFI/BT | double frequency WIFI/BT4.1 |
| | 4G/3G | 4G full Netcom |
| | RJ45 | 100M |
| swiping card | Card reader | Support IC |
| Audio | Audio | Left and right dual channel output, support 8R*3W dual speakers |
| | MIC | Support |
| QR code scanner | imaging sensor | 640×480 CMOS : 120FPS |
| | illumination | White light LED (6500K) |
| | Symbologies | 2D/1D |
| | Precision | ≥5mil |
| | Barcode sensitivity** | Tilt ±55° , Spin±55° , rotate 360° |
| | communication interface | USB |
| | Operating voltage/current | 5V DC±10% (typical) Less than 190mA (5V input) Less than 100mA (10V input) |
| Built-in camera | photosensitive element | CMOS |



Hợp tác để thành công

CÔNG TY CỔ PHẦN THƯƠNG MẠI VÀ SẢN XUẤT TOÀN AN KHÁNH

Số 4, ngách 2, ngõ 199 Hồ Tùng Mậu, Cầu Diễn, Nam Từ Liêm, Hà Nội

Tel: 024 3227 2296

Email: contact@toanankhanh.com.vn, Web: www.toanankhanh.com.vn

| | | | |
|----------------------------|----------------------------------------------|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | articulation Prime lens | | 200W pixel 1920*1080fhd |
| | articulation Prime lens In vivo detection | 7cm | PDF417, Data Matrix, QR Code |
| | | bioassay | Interleaved 2 of 5, ISBN, Code 93, Code 11,UCC/EAN-128 GS1 Databar, Matrix 2 of 5, Industrial 2 of 5,Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar,Standard 2 of 5, MSI-Plessey,GS1 composite code, so on. |
| | output format | | YUV/MJPEG.H.264 |
| | white balance | | automatic |
| | illuminance | | Min 0.1LUX |
| | Operating environment | temperature | 5°C—40°C |
| relative humidity | | <80% (no condensation on the surface) | |
| Storage environment | temperature | -10°C—55°C | |
| | relative humidity | <70% (no condensation on the surface) | |
| Dimension | | | |

